


# CABLE TIES

**4" TO 48"**  
**HIGH QUALITY**  
**AMERICAN MADE**  
**UV STABILIZED**  
**NYLON 6/6**




Call or FAX Us for  
 Military Specification Numbers

**Available in Black or Natural**

Part #	Length	Bundle Dia.(Max)	Tensile Strength	Width	Thick-ness	\$/100	\$/500	\$/1000
CT4	4.0"	7/8"	18 Lbs.	.094"	.042"	\$1.35	\$6.15	\$11.18
CT6	5.7"	1 7/16"	40 Lbs.	.140"	.049"	2.74	12.46	22.66
CT8	7.5"	1 7/8"	50 Lbs.	.178"	.053"	3.16	14.37	26.11
CT8HD	7.5"	1 7/8"	120 LBS	.300"	.075"	10.30	46.81	85.10
CT11	11.2"	3 1/16"	50 Lbs.	.178"	.053"	5.63	25.61	46.55
CT14	14.5"	4 1/8"	50 Lbs.	.178"	.053"	7.74	35.18	63.95
CT14HD	15.0"	4 1/16"	120 Lbs.	.300"	.075"	14.23	64.68	117.60
CT24	25.3"	7 3/16"	175 Lbs.	.340"	.090"	24.96	113.45	206.28
CT36	37.1"	11 1/8"	175 Lbs.	.340"	.090"	31.97	145.32	264.21
CT48*	47.83"	14 1/2"	175 Lbs.	.340"	.090"	46.56	211.63	384.77

\* CT48 ALSO AVAILABLE IN GREY

# Mounting Hole CABLE TIES



MHCT6 uses a #8 Screw,  
 MHCT14H a 1/4" Screw.  
 All others use a #10 Screw.

**Available in Black or Natural**

Part #	Length	Bundle Dia.(Max)	Tensile Strength	Width	Thick-ness	\$/100	\$/500	\$/1000
MHCT6	5.7"	1 7/16"	30 Lbs.	.140"	.049"	\$4.75	\$21.62	\$39.29
MHCT8	7.5"	1 7/8"	50 Lbs.	.178"	.053"	5.35	24.28	44.13
MHCT11	11.2"	3 1/16"	50 Lbs.	.178"	.053"	12.07	54.84	99.70
MHCT14	14.5"	4 1/8"	50 Lbs.	.178"	.053"	15.26	69.34	126.08
MHCT14H	15.0"	4 1/16"	120 Lbs.	.300"	.075"	17.99	81.75	148.63



**1-800-645-5393 1-516-377-8787**  
**FAX 1-516-377-8733**