

STARTER CABLE

- **AMERICAN MADE**



- Fine Stranding for High Current Capacity*
- Tough PVC Insulation, Acid & Oil Resistant
- Meets SAE J1127, For Temperatures to 176° F.
- Available in: BLACK or RED *3/0 in black only

Part #	Gauge	Length	Price
EP4600	6	25'	\$31.85
EP4602	6	100'	106.81
EP4606	4	25'	40.60
EP4608	4	100'	142.97
EP4612	2	25'	66.56
EP4614	2	100'	254.89
EP4618	1	25'	77.55
EP4620	1	100'	298.66
EP4624	1/0	25'	97.59
EP4626	1/0	100'	378.83
EP4630	2/0	25'	116.00
EP4632	2/0	100'	452.67
EP4636*	3/0	25'	157.53
EP4637*	3/0	100'	613.23

*STRANDING: 6 GA.: 49/23ga, 4 GA.:70/23ga, 2 GA.:133/23ga.
1 GA.:133/22ga, 1/0 GA.:133/21ga, 2/0GA.:133/20ga, 3/0 GA.:259/22ga.

AWG TINNED STARTER CABLE

EXTRA FLEXIBLE STRANDING

- **AMERICAN MADE**
- **AWG, TINNED COPPER STRANDING***
SUPER FINE STRANDING provides increased flexibility as well as protection against corrosion, electrolysis & fatigue
- **Meets UL 1426, USCG & ABYC Specs** for Electrical Systems
- **105°C., 600 VOLT RATED INSULATION** resists acids, gas, oil, & UV rays
- **Available in: BLACK, RED or YELLOW**

Part #	Gauge	Length	Price
TSC825*	8	25'	\$19.34
TSC8*	8	100'	70.31
TSC625*	6	25'	30.39
TSC6*	6	100'	110.52
TSC425	4	25'	44.29
TSC4	4	100'	161.07
TSC225	2	25'	71.41
TSC2	2	100'	259.68
TSC125	1	25'	88.17
TSC1	1	100'	320.61
TSC025	0	25'	115.78
TSC0	0	100'	421.01
TSC2025	2/0	25'	135.36
TSC20	2/0	100'	492.21
TSC3025	3/0	25'	170.14
TSC30	3/0	100'	618.68
TSC4025	4/0	25'	211.56
TSC40	4/0	100'	769.31

*#6 & #8 Ga. Also in GREEN, ORANGE or WHITE

STRANDING: 8GA.:168/30ga, 6 GA.: 266/30ga, 4 GA.:420/30ga. 2 GA.:665/30ga.
1 GA.:836/30ga, 1/0 GA.:1064/30ga, 2/0GA.:1330/30ga. 3/0 GA.:1672/30ga. 4/0 GA.:2107/30ga.



1-800-645-5393 1-516-377-8787
FAX 1-516-377-8733