

Bullet Snap Plugs



PART#	WIRE	RANGE	DESCRIPTION	\$/25	\$/50	\$/100	\$/500
ANRSM156	22-18	RED	.156 Male, NYLON	\$5.83	\$10.60	\$19.27	\$87.60
ANRSF156	22-18	RED	.156 Female, NYLON	6.44	11.70	21.27	96.70
ANBSM156	16-14	BLUE	.156 Male, NYLON	5.83	10.60	19.27	87.60
ANBSF156	16-14	BLUE	.156 Female, NYLON	6.44	10.28	18.69	84.96

Female Quick Disconnects



PART#	WIRE	RANGE	DESCRIPTION	\$/25	\$/50	\$/100	\$/500
ANRF250	22-18	RED	.250 Female, NYLON	\$4.42	\$8.04	\$14.63	\$66.48
ANBF250	16-14	BLUE	.250 Female, NYLON	4.42	8.04	14.63	66.48
ANYF250	12-10	YELLOW	.250 Female, NYLON	5.65	10.24	17.06	77.55


Male Quick Disconnects*



* ZINC CHROMIUM PLATED

PART#	WIRE	RANGE	DESCRIPTION	\$/25	\$/50	\$/100	\$/500
ANRM250	22-18	RED	.250 Male, NYLON	\$4.56	\$8.29	\$15.07	\$68.48
ANBM250	16-14	BLUE	.250 Male, NYLON	5.05	9.18	16.70	75.90
ANYM250	12-10	YELLOW	.250 Male, NYLON	5.65	10.28	18.69	84.95

Fully Insulated Disconnects



PART#	WIRE	RANGE	DESCRIPTION	\$/25	\$/50	\$/100	\$/500
ANRMI	22-18	RED	Nylon Male .250	\$6.04	\$10.98	\$19.96	\$90.72
ANRFI	22-18	RED	Nylon Female .250	5.75	10.45	19.01	86.39
ANBMI	16-14	BLUE	Nylon Male .250	6.04	10.98	19.96	90.72
ANBFI	16-14	BLUE	Nylon Female .250	5.75	10.45	19.01	86.39
ANYMI	12-10	YELLOW	Nylon Male .250	8.33	15.14	27.53	125.12
ANYFI	12-10	YELLOW	Nylon Female .250	7.99	14.52	26.41	120.04

Piggy Backs



PART#	WIRE	RANGE	DESCRIPTION	\$/25	\$/50	\$/100	\$/500
ANRPB	22-18	RED	Piggy Back, NYLON	\$6.74	\$12.26	\$22.28	\$101.29
ANBPB	16-14	BLUE	Piggy Back, NYLON	6.79	12.35	22.46	102.07
ANYPB	12-10	YELLOW	Piggy Back, NYLON	7.87	14.32	26.03	118.32

Fully Insulated Piggy Backs



PART#	WIRE	RANGE	DESCRIPTION	\$/25	\$/50	\$/100	\$/500
ANRPBI	22-18	RED	Ins. Piggy Back, NYLON	\$8.94	\$16.25	\$29.55	\$134.33
ANBPBI	16-14	BLUE	Ins. Piggy Back, NYLON	9.73	17.70	32.18	146.25
ANYPBI	12-10	YELLOW	Ins. Piggy Back, NYLON	10.48	19.06	34.65	157.50



1-800-645-5393 1-516-377-8787
FAX 1-516-377-8733